

Flame Retardant ABS

[Flame retardant solutions]
with material property balance



Key Features



Flammability



Heat stability



Processability



Colorability

PRODUCT LINE-UP

TBBA	Non-TBBA	Non-Halogen
<ul style="list-style-type: none"> 1.5mm V-0 <ul style="list-style-type: none"> └ VH-0816 2.0mm V-0 <ul style="list-style-type: none"> └ VH-0815 2.5mm V-0 <ul style="list-style-type: none"> └ VH-0810 T 	<ul style="list-style-type: none"> 1.5mm V-0 <ul style="list-style-type: none"> └ VE-0800 └ VE-0856 (2.0mm 5VB, 3.0mm 5VA, RTI 80°C) └ VE-0860 (2.5mm 5VB, RTI 95°C) └ VE-0870 (2.0mm 5VA) └ VE-0871 (2.0mm 5VA) └ VE-0880* (1.5mm 5VA) └ VE-0873EX (2.0mm, 5VA, Extrusion) 2.0mm V-0 <ul style="list-style-type: none"> └ VE-0815 2.5mm V-0 <ul style="list-style-type: none"> └ VE-0800 T 	<ul style="list-style-type: none"> 2.0mm V-0 <ul style="list-style-type: none"> └ VE-0815 └ VE-0865 (2.5mm 5VA) 2.1mm V-0 <ul style="list-style-type: none"> └ VE-0858 2.5mm V-0 <ul style="list-style-type: none"> └ VE-0810 3.0mm V-2 <ul style="list-style-type: none"> └ VE-0865EL (Extrusion) 1.0mm V-2 <ul style="list-style-type: none"> └ NH-0927

* Under Development